

# DIABLO




<b>Colours</b>	■ ■
<b>Housing</b>	Aluminium, die cast
<b>Fixture type</b>	Track light
<b>Module</b>	Philips Fortimo SLM LED module
<b>Driver</b>	Powergear® adapter with build-in LED driver
<b>Light Output module</b>	1100lm, 2000lm, 3000lm
<b>CCT</b>	2700K, 3000K, 4000K, 5700K
<b>CRI</b>	>80Ra, >90Ra
<b>Beam angles</b>	15°, 24°, 40°, 60°
<b>Adapter</b>	Powergear® 3-phase Ultimate adapter included
<b>Rotatable</b>	350°
<b>Tilttable</b>	90°
<b>LED modules</b>	Standard, Premium
<b>Dimming Options</b>	DALI, Casambi
<b>Options</b>	Honeycomb, Glass
<b>Expected Lifetime</b>	>50.000h (L90/B50)
<b>Photobiological safety</b>	RG1 unlimited
<b>Power factor</b>	> 0.9
<b>LOR</b>	> 90%
<b>Colour consistency</b>	3 SDCM
<b>Warranty</b>	5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
425 grams	24 x 18 x 11 cm	18

## Available LED Modules

**PHILIPS**  
LED SLM INSIDE

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Philips Fortimo SLM G7	1100lm	7W	157	827, 830	>80						
Philips Fortimo SLM G7	1100lm	6W	183	840, 857	>80						
Philips Fortimo SLM G7	1100lm	8W	138	927,930,930PW	>90						
Philips Fortimo SLM G7	1100lm	7W	157	940PW	>90						
Philips Fortimo SLM G7	2000lm	15W	167	827, 830	>80						
Philips Fortimo SLM G7	2000lm	12W	167	840, 857	>80						
Philips Fortimo SLM G7	2000lm	15W	133	927, 930, 930PW	>90						
Philips Fortimo SLM G7	2000lm	14W	143	940 PW	>90						
Philips Fortimo SLM G7	3000lm	19W	158	827, 830	>80						
Philips Fortimo SLM G7	3000lm	18W	166	840, 857	>80						
Philips Fortimo SLM G7	3000lm	22W	136	927, 930, 930PW	>90						
Philips Fortimo SLM G7	3000lm	20W	150	940PW	>90						



### LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.



**INTERNOVA**  
PROFESSIONAL LIGHTING