







# LUCEVARIA PENDANT

PENDANT LIGHTING

made in  
**HOLLAND**

AVAILABLE IN

|              | Reflector   | Led module  |   | Dim options   |   |   |
|--------------|---|---|---|---|---|---|
|              | Reflector   | Standard  | TW  | Dimmable  | Dimmable  | Casambi   |
|              |  |  |  |  |  |  |
| Lumen output |   |   |   | 1130mm:   |   | 3000lm  |
|              |   |   |   | 1410mm:   |   | 3850lm  |
|              |   |   |   | 1970mm:   |   | 6000lm  |
| CRI          |   |   |   | >80Ra • >90Ra   |   |   |
| CCT          |   |   |   | 3000K • 4000K   |   |   |

## FIXTURE SPECIFICATIONS

 [View product on website](#)

|                         |   |
|-------------------------|---|
| Housing material        | Die cast aluminium                        |
| Material finish         | Powder coating                            |
| RAL colour              | 9004 (Black) • 9003 (White) • 9006 (Grey) |
| Fixture type            | Pendant light                             |
| LED Module              | Osram PrevaLED G6                         |
| Driver                  | Philips Xitanium LED driver               |
| Number of light sources | 1   |
| IP rating               | IP20                                      |
| Expected lifetime       | L80 / B50 @ 70.000 hours                  |
| Photobiological safety  | RG1 Unlimited                             |
| UGR                     | < 23                                      |
| Power factor            | > 0.9                                     |
| Colour consistency      | 3 SDCM                                    |
| Warranty                | 5 years on LED module and driver          |

Fixture weight:  
Suspension 300 cm



## FIXTURE VARIATIONS

| LED module        | Lumen  | Light colour | Efficiency (Lm/W) | Power | Dim options    |
|-------------------|--------|--------------|-------------------|-------|----------------|
| Osram PrevaLED G6 | 1500lm | 830 / 840    | 136 / 136         | 12.0W | DALI / Casambi |
| Osram PrevaLED G6 | 1500lm | 930          | 100               | 15.0W | DALI / Casambi |
| Osram PrevaLED G6 | 1500lm | 940          | 115               | 15.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3000lm | 830 / 840    | 136 / 136         | 24.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3000lm | 930          | 100               | 29.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3000lm | 940          | 120               | 29.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3850lm | 830 / 840    | 128 / 128         | 30.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3850lm | 930          | 99                | 36.0W | DALI / Casambi |
| Osram PrevaLED G6 | 3850lm | 940          | 113               | 36.0W | DALI / Casambi |

Fixture variations:

- <sup>1)</sup> Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- <sup>2)</sup> Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- <sup>3)</sup> Fixture efficiency is displayed in lumens per watt and is calculated based on the net lumen output and power consumption of both the LED module and driver.
- <sup>4)</sup> Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting BV without prior notice.

## ARTICLE CODE CONFIGURATOR

IN

**FIXTURE LENGTH**

**LIGHT COLOUR**

**REFLECTOR**

**FIXTURE COLOUR**

**DIM OPTIONS**

**LUMEN OUTPUT**

Article code configurator:

- <sup>1)</sup> This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome