



INTERNOVA

PROFESSIONAL LIGHTING

LOGICA

made in
HOLLAND


Colours	☐ ■
Housing	Aluminium, die cast
Fixture type	Track light
Module	Philips Fortimo SLM VO LED module
Driver	Driver incorporated in track adapter
Light Output module	1100lm, 2000lm, 3000lm
CCT	3000K, 4000K
CRI	>80Ra, >90Ra
Beam angles	15°, 24°, 45°, 60°
Adapter	Powergear® 3-phase Ultimate adapter included
Rotatable	355°
Tiltable	90°
LED modules	Philips Value Output
Dimming Options	DALI, Casambi
Options	Honeycomb, Glass
Expected Lifetime	50.000h (L80/B10)
Photobiological safety	RG1 unlimited
Power factor	> 0.9
LOR	> 90%
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver



Net Weight	Dimensions carton L x W x H	Qty outer carton
425 grams	24 x 18 x 11 cm	18

Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI
Philips Fortimo SLM VO	1100lm	6,3W	175	830	>80
Philips Fortimo SLM VO	1100lm	6W	183	840	>80
Philips Fortimo SLM VO	1100lm	7,6W	145	930	>90
Philips Fortimo SLM VO	1100lm	7W	157	940	>90
Philips Fortimo SLM VO	2000lm	12,7W	157	830	>80
Philips Fortimo SLM VO	2000lm	12W	167	840	>80
Philips Fortimo SLM VO	2000lm	15,4W	130	930	>90
Philips Fortimo SLM VO	2000lm	14,3W	140	940	>90
Philips Fortimo SLM VO	3000lm	21,3W	141	830	>80
Philips Fortimo SLM VO	3000lm	19,9W	151	840	>80
Philips Fortimo SLM VO	3000lm	26,5W	113	930	>90
Philips Fortimo SLM VO	3000lm	24,2W	124	940	>90



LED modules

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour

temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.



Internova.nl