

SNELLO



Colours	Aluminium, die cast
Housing	Surface mounted
Fixture type	Philips Fortimo SLM LED module
Module	Philips Xitanium LED driver
Driver	1100lm, 2000lm, 3000lm
Light Output module	2200K 2700K, 3000K, 4000K, 5700K
CCT	>80Ra, >90Ra
CRI	15°, 24°, 40°
Beam angles	Standard, Premium, DTW
LED modules	TRIAC, DALI, 1-10V, Casambi
Dimming Options	>50.000h (L90/B50)
Expected Lifetime	RG1 unlimited
Photobiological safety	> 0.9
Power factor	> 90%
LOR	3 SDCM
Colour consistency	5 years warranty on LED module and driver
Warranty	

Net Weight	Dimensions carton L x W x H	Qty outer carton
1671 grams	23 x 13 x 14 cm	12

Available LED Modules

PHILIPS
LED SLM INSIDE

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Philips Fortimo SLM G7	1100lm	7W	157	827, 830	>80						
Philips Fortimo SLM G7	1100lm	6W	183	840, 857	>80						
Philips Fortimo SLM G7	1100lm	8W	138	927,930,930PW	>90						
Philips Fortimo SLM G7	1100lm	7W	157	940PW	>90						
Philips Fortimo SLM G7	1100lm	10W	110	922 PA (2200K)	>90						
Dim-To-Warm (DTW)	1100lm	13W	85	2200-3000K	>90						
Philips Fortimo SLM G7	2000lm	15W	167	827, 830	>80						
Philips Fortimo SLM G7	2000lm	12W	167	840, 857	>80						
Philips Fortimo SLM G7	2000lm	15W	133	927, 930, 930PW	>90						
Philips Fortimo SLM G7	2000lm	14W	143	940 PW	>90						
Philips Fortimo SLM G7	2000lm	19W	105	922 PA (2200K)	>90						
Dim-To-Warm (DTW)	1900lm	20W	95	2200-3000K	>90						
Philips Fortimo SLM G7	3000lm	19W	158	827, 830	>80						
Philips Fortimo SLM G7	3000lm	18W	166	840, 857	>80						
Philips Fortimo SLM G7	3000lm	22W	136	927, 930, 930PW	>90						
Philips Fortimo SLM G7	3000lm	20W	150	940PW	>90						
Philips Fortimo SLM G7	3000lm	31W	96	922 PA (2200K)	>90						



LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.



INTERNOVA
PROFESSIONAL LIGHTING