











TORRENTE

RECESSED LIGHTING

made in
HOLLAND

AVAILABLE IN



Standard	Reflector				Led module		Dim options	
Dimmable	Reflector	Reflector	Reflector	Reflector	Standard	DTW	Dimmable	Casambi
								
Fixture options								
Honeycomb								
								

Lumen output	1100lm
CRI	>90Ra
CCT	2700K • 3000K

FIXTURE SPECIFICATIONS

 [View product on website](#)

Fixture weight: 428 grams
Cut out size: ø75 x 90mm



FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
Bridgelux V6 HD	1100lm	927	86	15.5W	Triac / DALI / Casambi
Bridgelux V6 HD	1100lm	930	93	15W	Triac / DALI / Casambi
Bridgelux V6 HD	1100lm	Dim to Warm • 1800K - 3000K	89	14.5W	Triac / DALI / Casambi

Fixture variations:

- ¹⁾ Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- ²⁾ Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- ³⁾ Fixture efficiency is displayed in lumens per watt and is calculated based on the gross lumen output and power consumption of both the LED module and driver
- ⁴⁾ Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting without prior notice.

ARTICLE CODE CONFIGURATOR

IN

FIXTURE TYPE

LIGHT COLOUR

REFLECTOR

FIXTURE COLOUR

DIM OPTIONS

LUMEN OUTPUT

STANDARD

OPTIONS

Article code configurator:

- ¹⁾ This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome

POLAR

DIAGRAMS

