

GALLERIA



Colours	☐ ■
Housing	Aluminium, die cast
Fixture type	Track light
Module	Philips Fortimo SLM LED module
Driver	Philips Xitanium LED driver
Light Output module	1100lm, 2000lm
CCT	2700K, 3000K, 4000K, 5700K
CRI	>80Ra, >90Ra
Beam angles	15°, 20°, 30°
Adapter	Powergear® 3-phase adapter included
Rotatable	350°
Tilttable	90°
LED modules	Standard
Dimming Options	DALI
Expected Lifetime	>50.000h (L90/B50)
Photobiological safety	RG1 unlimited
Power factor	> 0.9
LOR	> 90%
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
691 grams	14 x 15 x 17 cm	12

Available LED Modules

PHILIPS
LED SLM INSIDE

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Philips Fortimo SLM G7	1100Lm	7W	157	827, 830	>80						
Philips Fortimo SLM G7	1100lm	6W	183	840, 857	>80						
Philips Fortimo SLM G7	1100lm	8W	138	927,930,930PW	>90						
Philips Fortimo SLM G7	1100lm	7W	157	940PW	>90						
Philips Fortimo SLM G7	2000lm	15W	167	827, 830	>80						
Philips Fortimo SLM G7	2000lm	12W	167	840, 857	>80						
Philips Fortimo SLM G7	2000lm	15W	133	927, 930, 930PW	>90						
Philips Fortimo SLM G7	2000lm	14W	143	940 PW	>90						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments


¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.



INTERNOVA
PROFESSIONAL LIGHTING