


LINEA
TRACK LIGHTING

made in
HOLLAND

AVAILABLE IN



Lumen output	Linea60:	2200lm
	Linea100:	3200lm
CRI	>80Ra	
CCT	Switchable	3000K / 4000K / 5700K

FIXTURE SPECIFICATIONS

 [View product on website](#)

Housing material	Plastic
Material finish	Matte coating
RAL colour	9005 (Black) • 9016 (White)
Fixture type	3-phase track light
LED Module	Osram V-S LED Linear
Driver	Osram V-S comfort line
Adapter	Powergear 3-circuit track adapter
Number of light sources	1
IP rating	IP20
Expected lifetime	L90 / B10 @ 50.000 hours
Photobiological safety	RG1 Unlimited
Power factor	> 0.9
Colour consistency	≤6 SDCM
Warranty	3 years on LED module and driver

Fixture weight:





FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
Osram V-S LED Linear 60cm	1560lm	830 / 840 / 857	98	16.0W	N/A
Osram V-S LED Linear 100cm	3000lm	830 / 840 / 857	100	30.0W	N/A

Fixture variations:

- ¹⁾ Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- ²⁾ Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- ³⁾ Fixture efficiency is displayed in lumens per watt and is calculated based on the net lumen output and power consumption of both the LED module and driver.
- ⁴⁾ Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting BV without prior notice.

ARTICLE CODE CONFIGURATOR

IN

FIXTURE LENGTH

FIXTURE COLOUR

LUMEN OUTPUT

Article code configurator:

- ¹⁾ This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome