

LUCEVARIA PENDANT

PENDANT LIGHTING

AVAILABLE IN

 made in
HOLLAND

Reflector	Led module		Dim options		
Reflector	Standard	TW	Dimmable	Dimmable	Casambi
					
Lumen output	570mm:		1500lm		
	1130mm:		3000lm		
	1410mm:		3850lm		
	1970mm:		6000lm		
CRI	>80Ra • >90Ra				
CCT	3000K • 4000K				

FIXTURE SPECIFICATIONS

[View product on website](#)

Fixture weight: Suspension 300 cm      	Housing material	Die cast aluminium
	Material finish	Powder coating
	RAL colour	9004 (Black) • 9003 (White) • 9006 (Grey)
	Fixture type	Pendant light
	LED Module	Osram PrevaLED G6
	Driver	Philips Xitanium LED driver
	Number of light sources	1
	IP rating	IP20
	Expected lifetime	L80 / B50 @ 70.000 hours
	Photobiological safety	RG1 Unlimited
	UGR	< 23
	Power factor	> 0.9
	Colour consistency	3 SDCM
	Warranty	5 years on LED module and driver



FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
Osram PrevaLED G6	1500lm	830 / 840	136 / 136	12.0W	DALI / Casambi
Osram PrevaLED G6	1500lm	930	100	15.0W	DALI / Casambi
Osram PrevaLED G6	1500lm	940	115	15.0W	DALI / Casambi
Osram PrevaLED G6	3000lm	830 / 840	136 / 136	24.0W	DALI / Casambi
Osram PrevaLED G6	3000lm	930	100	29.0W	DALI / Casambi
Osram PrevaLED G6	3000lm	940	120	29.0W	DALI / Casambi
Osram PrevaLED G6	3850lm	830 / 840	128 / 128	30.0W	DALI / Casambi
Osram PrevaLED G6	3850lm	930	99	36.0W	DALI / Casambi
Osram PrevaLED G6	3850lm	940	113	36.0W	DALI / Casambi

Fixture variations:
1) Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
2) Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
3) Fixture efficiency is displayed in lumens per watt and is calculated based on the net lumen output and power consumption of both the LED module and driver.
4) Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting BV without prior notice.

ARTICLE CODE CONFIGURATOR

IN

82

FIXTURE LENGTH

LIGHT COLOUR

REFLECTOR

FIXTURE COLOUR

DIM OPTIONS

LUMEN OUTPUT

Article code configurator:
1) This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome