## CAMBIA







Net Weight	Dimensions carton L x W x H	Qty outer carton			
750 grams	20 x 19 x 12 cm	20			

Housing Aluminium, die cast **RAL** colour 9004 (Black), 9003 (White) Fixture type 3-phase track light Module Luminus LED

Powergear® Ultimate adapter with build-in LED driver Driver Lumen output

1100lm, 2000lm

>90Ra

10º - 60º (adjustable beam angle) Beam angles

Powergear® 3-phase ultimate adapter included

90º

Tiltable **Expected Lifetime** >40.000h (L70/B30) **Photobiological safety** RG1 unlimited

> 0.9 Power factor

> 90% UGR 3 SDCM Colour consistency

Warranty

5 years warranty on LED module and driver

## LED MODULES

Standard



## **OPTIONS**

Dimmable

Casambi





## LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Luminus LED	1100Lm	17W	85	930, 940	>90Ra						
Luminus LED	2000Lm	25W	80	930, 940	>90Ra						

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3</sup>) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light

<sup>&</sup>lt;sup>2</sup>) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.