



Housing	Aluminium
RAL colour	9004 (Black), 9003 (White), 1036 (Gold)
Fixture type	Surface mounted
Module	Citizen LED
Driver	Osram TRIAC dimmable driver
Lumen output	1500lm
CCT	2700K
CRI	>90Ra
Beam angles	50°
Expected Lifetime	L80B10 >70.000 / L90B50 >50.000h
Photobiological safety	RG1 unlimited
Power factor	> 0.9
UGR	< 19
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver

Also available with Powergear® 3-phase track adapter

Net Weight	Dimensions carton L x W x H	Qty outer carton
850 grams	15 x 15 x 15 cm	14

LED MODULES

Standard



OPTIONS

Dimmable



LED MODULE OPTIONS

[illegible]

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light