



Housing	Aluminium, die cast
RAL colour	9004 (Black), 9003 (White)
Fixture type	Surface mounted
Module	Dim-to-Warm LED module
Driver	Osram TRIAC dimmable driver
Lumen output	900lm
CCT	DTW (3000K – 1800K)
CRI	>90Ra
Beam angles	40°
Rotatable	Cardanic
Tiltable	30°
Expected Lifetime	>30.000h (L70/B30)
Photobiological safety	RG1 unlimited
Power factor	> 0.9
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
621 grams	15 x 15 x 14 cm	24

LED MODULES

Standard



OPTIONS

LED MODULE OPTIONS

[illegible]

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

^{a)} Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light