LED PANEL NLO





Housing Aluminium, die cast **RAL** colour 9003 (White) Recessed Fixture type Module CREE LED Lumen output 3750lm, 3850lm 3000K, 4000K CCT >80Ra CRI 90º

Beam angles >50.000h (L90/B50) **Expected Lifetime RG1** unlimited **Photobiological safety** Power factor > 0.9 3 SDCM Colour consistency

3 years warranty on LED module and driver Warranty

Net Weight	Dimensions carton L x W x H	Qty outer carton			
2302 grams	70 x 65 x 7 cm	4			

LED MODULES

Standard



OPTIONS

Dimmable

Dimmable

Emergency unit







LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
CREE LED	3570Lm	35W	102	830	>80Ra						
CREE LED	3850Lm	35W	110	840	>80Ra						

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)
2) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light