



- Housing
- RAL colour
- Fixture type
- Module
- Driver
- Lumen output
- CCT
- CRI
- Beam angles
- Rotatable
- Tilttable
- Expected Lifetime
- Photobiological safety
- Power factor
- Colour consistency
- Warranty

Aluminium, die cast
9004 (Black), 9003 (White)
Surface mounted
Dim-to-Warm LED module
Osram TRIAC dimmable driver
900lm
DTW (3000K – 1800K)
>90Ra
40°
Cardanic
30°
>30.000h (L70/B30)
RG1 unlimited
> 0.9
3 SDCM
5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
595 grams	13 x 15 x 13 cm	20

LED MODULES

Standard



OPTIONS

LED MODULE OPTIONS

[illegible]

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light