



200

Ø 245

- Housing
- RAL colour
- Fixture type
- Module
- Driver
- Lumen output
- CCT
- CRI
- Beam angles
- Expected Lifetime
- Photobiological safety
- Power factor
- LOR
- Colour consistency
- Warranty

Aluminium, die cast
9004 (Black), 9003 (White)
Surface mounted
Philips Fortimo DLM FLEX G2 LED module
Philips Xitanium external LED driver with strain relief
1100lm, 2000lm, 3000lm
3000K, 4000K
>80Ra
70°
L80B10 >70.000 / L90B50 >50.000h
RG1 unlimited
> 0.9
> 90%
3 SDCM
3 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
1352 grams	26 x 26 x 26 cm	8

LED MODULES

Standard



OPTIONS

Dimmable

Dimmable

Dimmable

Casambi



LED MODULE OPTIONS

[illegible]

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour

temperature is subject to a tolerance of up to ± 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light