## **SALINA**







Net Weight	Dimensions carton L x W x H	Qty outer carton			
550 grams	9 x 7 x 58 cm	10			

Housing Aluminium

**RAL colour** 9004 (Black), 9003 (White), 1036 (Gold)

Fixture type Pendant lighting
Module Citizen LED

**Driver** TRIAC dimmable driver incorporated in ceiling cap

 Lumen output
 600lm

 CCT
 2700K

 CRI
 >90Ra

 Beam angles
 50º

Expected Lifetime >40.000h (L70/B30)
Photobiological safety RG1 unlimited

Power factor > 0.9 UGR < 19 Colour consistency 3 SDCM

Warranty 3 years warranty on LED module and driver

Also available with Powergear® 3-phase track adapter

## **LED MODULES**

Standard



## **OPTIONS**

## **LED MODULE OPTIONS**

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Citizen LED	600Lm	7W	85	927	>90Ra						

LED module:

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

It all starts with light

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.
The power of the complete fixture will be slightly higher due to the power consumption of the driver