VARIAR







Net Weight	Dimensions carton L x W x H	Qty outer carton			
625 grams	20 x 8 x 18 cm	10			

Housing Aluminium, die cast **RAL colour** 9004 (Black), 9003 (White) 3-phase track light Fixture type Module America Delux LED

Powergear® Ultimate adapter with build-in LED driver Driver 900lm Lumen output

2700K, 3000K >90Ra

8º - 30º (adjustable beam angle) Beam angles

Powergear® 3-phase ultimate adapter included Adapter

Rotatable 90⁰ Tiltable

Expected Lifetime >40.000h (L70/B30) **Photobiological safety** RG1 unlimited > 0.9 Power factor

< 19 UGR 3 SDCM Colour consistency

Warranty 5 years warranty on LED module and driver

LED MODULES

Standard



OPTIONS

Dimmable Casambi





LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
America Delux LED	900Lm	18W	50	927, 930	>90Ra						

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light

²) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.