







Net Weight Dimensions carton L x W x H Qty outer carton 280 grams 11 x 11 x 9 cm 30

Housing **RAL colour** Fixture type Module Driver Lumen output ССТ CRI Beam angles Rotatable Tiltable Cut out size Expected Lifetime Photobiological safety Power factor LOR Colour consistency Warranty

OPTIONS

Dimmable

DALI

Dimmable

1-10V

Casambi

Dimmable

TRIAC

Aluminium, die cast 9004 (Black), 9003 (White), Brushed Aluminium Recessed Dim-to-Warm LED module TRIAC dimmable driver 520lm DTW (3000K - 1800K) >90Ra 40º 360º 30º ø76 x H50mm >35.000h (L70/B30) RG1 unlimited > 0.9 > 90% 3 SDCM 5 years warranty on LED module and driver

LED MODULES





LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Description	Lumen	wall	Lm/ w		CKI	Description	Lumen	vvall			CRI
Visione360 DTW	520Lm	7W	74	1800K-3000K	>90Ra						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

²) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver. ³) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour

temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light