

# ULTIMO



<b>Colours</b>	Aluminium, die cast
<b>Housing</b>	Track light
<b>Fixture type</b>	Luminus LED module
<b>Module</b>	Powergear® adapter with build-in LED driver
<b>Driver</b>	1100lm
<b>Light Output module</b>	3000K
<b>CCT</b>	>90Ra
<b>CRI</b>	24°, 40°
<b>Beam angles</b>	Powergear® 3-phase Ultimate adapter included
<b>Adapter</b>	350°
<b>Rotatable</b>	90°
<b>Tilttable</b>	Standard
<b>LED modules</b>	DALI, Casambi
<b>Dimming Options</b>	Glass (standard)
<b>Options</b>	35.000h (L70/B30)
<b>Expected Lifetime</b>	RG1 unlimited
<b>Photobiological safety</b>	> 0.9
<b>Power factor</b>	3 SDCM
<b>Colour consistency</b>	3 years on LED module, 5 years on Ultimate adapter
<b>Warranty</b>	

Net Weight	Dimensions carton L x W x H	Qty outer carton
535 grams	25 x 23 x 10 cm	40

## Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Luminus LED module	1100lm	7W	74	830	>80						

### LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

