

# STRETTO 1500



<b>Colours</b>	Aluminium
<b>Housing</b>	Track light
<b>Fixture type</b>	Osram LED module
<b>Module</b>	Driver on board COB
<b>Driver</b>	1500lm
<b>Light Output module</b>	3000K
<b>CCT</b>	>80Ra
<b>CRI</b>	37°
<b>Beam angles</b>	Powergear® 3-phase adapter included
<b>Adapter</b>	350°
<b>Rotatable</b>	90°
<b>Tilttable</b>	Standard
<b>LED modules</b>	N/A
<b>Dimming Options</b>	35.000h (L70/B30)
<b>Expected Lifetime</b>	RG1 unlimited
<b>Photobiological safety</b>	> 0.9
<b>Power factor</b>	3 SDCM
<b>Colour consistency</b>	3 years warranty on LED module and driver
<b>Warranty</b>	



Net Weight	Dimensions carton L x W x H	Qty outer carton
505 grams	25 x 12 x 10	18

## Available LED Modules

**OSRAM**  
LED Inside

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Osram LED module	1500lm	15W	100	830	>80						

### LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments


<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.



**INTERNOVA**  
PROFESSIONAL LIGHTING