METEORA
PENDANT

made in HOLLAND

INTER NOVA
PROFESSIONAL LIGHTING

Housing	Aluminium
RAL colour	9004 (Black), 9003 (White), 1036 (Gold)
Fixture type	Pendant lighting
Module	Bridgelux V10
Driver	TRIAC dimmable driver incorporated in ceiling cap
Lumen output	1100lm
CCT	2700K, 3000K
CRI	>90Ra
Beam angles	15º, 24°, 40°
Expected Lifetime	50.000h L80/B10
Photobiological safety	RG1 unlimited
Power factor	> 0.9
UGR	< 19
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver

Also available with Powergear® 3-phase track adapter

Net Weight	Dimensions carton L x W x H	Qty outer carton
On request	On request	On request

LED MODULES

Standard

OPTIONS

Dimmable

Casambi

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Bridgelux V10	1100Lm	15W	73	927, 930	>90Ra						

LED modules
Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K
Premium White (PW): for fresh white and depth of colour in retail environments
[1]) Lumen output of LED module (COB)
[2]) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.
The power of the complete fixture will be slightly higher due to the power consumption of the driver.
[3]) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.
Technical data can be changed by Internova without prior notice.

It all starts with light